

DESCRIPTION

Total thickness	EN 428	mm	2.00
Weight	EN 430	g/m ²	3680
Width of sheet	EN 426	cm	
Length of sheet	EN 426	lm	
Tile size	EN 427	mm	300 x 300
Number of tiles per package	-	-	50



CLASSIFICATION

Norm / Product specification	-	-	EN 649
European classification	EN 685	class	33 - 42
K rating	-	class	K4
Fire rating	EN 13 501-1	class	B _{fl} -s1
Critical radiant flux	ASTM E648	W/cm ²	
Marine Equipment Directive International Maritime Organisation	Directive 96/98/EC I.M.O code F.T.P.	n°	
Static electrical propensity	EN 1815	kV	< 2

PERFORMANCE

Wear resistance	EN 660.1	mm	0.45
Wear Group	EN 649	group	F
Dimensional stability	EN 434	%	≤ 0.25
Residual indentation	EN 433	mm	~ 0.03
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	class	OK
Anti-bacterial and fungicidal treatment	-	-	OK
Surface treatment	-	-	PU

CE MARKING

	EN 14041	-	
		-	