


Mipolam 150 (2mm)			
DESCRIPTION			
Total thickness	EN 428	mm	2
Weight	EN 430	g/m ²	3360
Width of sheet	EN 426	cm	200
Length of sheet	EN 426	lm	20
Tile size	EN 427	mm	
Number of tiles per package	-	-	
CLASSIFICATION			
Norm / Product specification	-	-	EN 649
European classification	EN 685	class	34 - 43
K rating	-	class	
Fire rating	EN 13 501-1	class	B _{fl} -s1
Critical radiant flux	ASTM E648	W/cm ²	
Marine Equipment Directive International Maritime Organisation	Directive 96/98/EC I.M.O code F.T.P.	n°	
Static electrical propensity	EN 1815	kV	2
Electrical resistance	EN 1081	Ohm	≥
PERFORMANCE			
Wear resistance	EN 660.1	mm	
Wear Group	EN 649	group	M
Dimensional stability	EN 434	%	0.40
Residual indentation	EN 433	mm	0.10
Thermal conductivity	EN 12 524	W/(m.K)	0,25
Colour fastness	EN 20 105 - B02	degree	6
Chemical products resistance	EN 423	class	OK
Anti-bacterial and fungicidal treatment	-	-	OK
Surface treatment	-	-	PU
CE MARKING			
	EN 14041	-	