



BENEFITS

QUICK AND EASY INSTALLATION

Exclusive vertical interlocking system
Install with a mallet... it's child play!

- No adhesive needed
- Can be trimmed with an utility knife

FOR HOUSEHOLD AND COMMERCIAL USE

European classification 33/42

RESISTANT

0.55 mm wear layer
Shock-resistant varnish
Fiberglass inside

IDEAL FOR RENOVATIONS

5 mm thick: doors don't have to be shortened
Direct laying on ceramic
(if joints < 4 mm wide and < 1 mm deep)

REALISTIC


Textured and matt finish surface
4 bevelled edges

SUITABLE FOR HIGH-HUMIDITY ROOMS

Watertight and slip-resistant

EASY TO CLEAN, ECONOMICAL AND ECO-FRIENDLY

Clean with soapy water or neutral detergent



TECHNICAL CHARACTERISTICS

		Planks	Tiles
THICKNESS	mm	5	5
WEAR LAYER THICKNESS	mm	0,55	0,55
WEIGHT	g/m ²	8260	8260
DIMENSIONS	cm	100 x 17,6	36 x 69,6
AREA PER BOX	m ²	1,76	1,75
PLANKS PER BOX	Planks/ Tiles	10	7
SURFACE		Varnished	Varnished
EUROPEAN CLASSIFICATION	Class	33 / 42	33 / 42
FIRE RATING	Class	BflS1	BflS1
SOUND INSULATION	dB	5	5
WATER RESISTANCE		Compatible with wet rooms	
RESIDENTIAL USE GUARANTEE*	year	15	15

* For more details on guarantee, see www.gerflor.com

INSTALLATION TIPS

- **TOOLS REQUIRED:** ruler, utility knife, tape measure and rubber mallet.
- **Check** that all planks have the same batch number.
- **Store** the planks in the room, flat and face up, for 24 hours prior to installation.
- **No underlay needed.**
- **Room temperature recommended** during installation: between 15°C and 25°C.
- **Temperature range accepted after installation:** minimum 10°C and up to 30°C
Over and above, planks must be glued

SUPPORT TOLERANCE	Flatness tolerance Step tolerance	≤ 5 mm under a 2 m ruler < 1 mm < 1 mm under a 20 cm ruler
INSTALLATION POSSIBILITIES ACCORDING TO SUBFLOOR*	On carpet On seamless tile (granite-type) On tile (with joints) On laminate On concrete On PVC (compact) On solid or engineered wood floor with ventilated underside	No Remove subfloor Yes Yes if joint < 4 mm wide and < 1 mm deep No Remove subfloor Yes Yes Yes if subfloor rigid & stable
HEATED FLOORING	> 28°C < 28°C Reversible Anhydrite coating	No Yes Yes Yes
EXPOSURE	Veranda Skylight	No Yes if planks are glued

* For more details on installation, see www.gerflor.com

ENVIRONMENT



HEALTH

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer
- Low VOC emission

ENVIRONMENT

- 100% recyclable
- Soapy water cleaning