

NERA CONTRACT WOOD

gerflor.com



Gerflor[®]
theflooringgroup

NERA CONTRACT WOOD

The warmth and style of a wood design combined with the performance of a vinyl floorcovering

- ▶ Retirement homes
- ▶ Hospitals, clinics
- ▶ Offices
- ▶ Commercial premises, professional premises
- ▶ Hotels, cafeterias



Colour reference	Colour name	Pattern repeat in mm	Planks sizes in cm	
			Length	Width
0592	OTTAWA POPLAR	1000x1000	31.5 - 33.5 - 35	6.2
0593	OREGON NATURAL	1000x1000	33.3 - 25 - 50	6.6
0594	DAKOTA AUTUMN	1333x1000	32 - 33	7 to 7.5
0590	ONTARIO MAPLE	1333x1000	61.5 - 30.7 - 40.5	7
0583	CADIX GOLD	1333x1000	66.3	9
0587	SATURNE CHERRY	1000x1000	20	5
0585	SATURNE PEROU	1000x1000	20	5
1200	BAMBOO TEA	1000x1000	continuous	1.8
1302	BLADE CLEAR	1000x1000	100	16.6
1309	NOMA RUSTIC	1000x1000	100	16.6
1310	SYCOMORE GOLDEN	1000x1000	100 - 54 - 46 - 44.5 - 55.5 - 38 - 62 - 47.3 - 52.7	12.5
1311	WENGUE SAFARI	1000x1000	100	10
1312	MAMBO ASH	1000x1000	100	10 - 11 - 12
1313	LOUNGE CHIC	1000x2000	50	2.5
1314	WALNUT BROWN	1000x1000	100	10




0593 Oregon Natural
WR: 0585 0496





0590 Ontario Maple
WR: 0585 0581



0592 Ottawa Poplar
WR: 0585 0485




1302 Blade Clear
WR: 0585 0896

 Without foam backing (Compact) -  Planks width in cm - WR: Welding Rods
2 - 4 m



SAMPLING SERVICE: Call Gerflor to request your samples!

NERA CONTRACT WOOD



1.8 cm



1200 Bamboo Tea
WR: 0585 2142



16.6 cm



1309 Noma Rustic
WR: 0585 2336



10-11-12 cm



1312 Mambo Ash
WR: 0585 0386



9 cm



0583 Cadix Gold
WR: 0585 2136



10 cm



1314 Walnut Brown
WR: 0585 2335



2 - 4 m

Without foam backing (Compact) -  Planks width in cm - WR: Welding Rods



1311 Wengue Safari
WR: 0585 2337




0594 Dakota Autumn
WR: 0585 2135




0585 Saturne Perou
WR: 0585 2132



1310 Sycamore Golden
WR: 0585 0657



0587 Saturne Cherry
WR: 0585 0676



1313 Lounge Chic
WR: 0585 0672



Without foam backing (Compact) -  Planks width in cm - WR: Welding Rods



SAMPLING SERVICE: Call Gerflor to request your samples!

PRODUCT BENEFITS



Durable

- The pure PVC wearlayer is abrasion resistant and carries a Group T rating.
- Suitable for normal to high traffic areas subject to the correct cleaning and maintenance.
- Excellent dimensional stability due to glass fibre reinforcement.

Excellent resistance to static and dynamic loads

- Excellent and rapid indentation recovery.
- Resistant to rucking even when heavy objects wheeled across the surface (hospital beds, trolleys etc.).

Warm and inviting rooms

- Highly recommended for heavy traffic areas: hospitals, retirement homes, offices, schools, shops etc.
- Authentic wood designs with realistic matt wood grain finish.
- 15 wood tones from rustic to exotic.

PUR: Polyurethane surface treatment

PUR

- Factory applied PUR surface treatment offers initial protection for the floor.
- Eases maintenance and avoids the application of acrylic emulsions/polish after installation.
- The subsequent intervals between polish applications will depend on the level of hygiene and cleanliness required.
- The use of chemical cleaning agents is accordingly reduced.



Hygiene

Sanosol®

- Suitable for use in humid and damp rooms.
- Resistant to mould and mildew.
- Non absorbent, impermeable and non porous.
- Treated with Sanosol® to prevent the growth of fungus, bacteria and micro-organisms.
- Available in 2 m and 4 m widths to reduce the need for hot welded seams.
- Can be installed with coved skirtings to provide a water tight finish.


Stain resistance

- PUR surface treatment offers an excellent stain resistance when compared to non treated equivalents.


Finishes

- Easy to install: installation by over lapping

Semi flexible skirting Vynaflex



Flexible skirting



Refer to the "Commercial flooring solutions" catalogue for accessories.




SAMPLING SERVICE: Call Gerflor to request your samples!

PRODUCT DESCRIPTION

▶ NERA CONTRACT WOOD

	PUR	Sanosol®	 100 % recyclable
---	-----	----------	--



NERA CONTRACT WOOD is a multilayered vinyl floorcovering, available in 2 m & 4 m wide sheet. The product comprises a compacted underlayer reinforced with glass fibre and a printed wood design that is protected by a transparent wood grain embossed wearlayer.

NERA CONTRACT WOOD is treated with a polyurethane treatment (PUR) that facilitates ease of maintenance and eliminates the need to use acrylic emulsion polishes after installation.

NERA CONTRACT WOOD has anti-static properties (AS Class 1) and is Sanosol® treated to prevent bacterial and fungal growth.

- 1 - PUR® treatment
- 2 - Transparent wood grain embossed wearlayer
- 3 - Printed design
- 4 - Glass fibre
- 5 - Compact layer
- 6 - Sanosol® treatment





SAMPLING SERVICE: Call Gerflor to request your samples!

TECHNICAL DATA

Nera Contract Wood

DESCRIPTION

Total thickness	EN 428	mm	2.25
Thickness of wearlayer	EN 429	mm	0.70
Weight	EN 430	g/m ²	2815
Width of sheet	EN 426	cm	200 / 400
Length of sheet	EN 426	lm	20





CLASSIFICATION

Norm / Product specification	-	-	EN 649
European classification	EN 685	class	34-43
Fire rating	EN 13 501 - 1	class	Bfl-s1
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet : ramp test with oil	DIN 51 130	class	R10

PERFORMANCE

Wear resistance	EN 660.2	mm ³	≤ 2.0
Wear group	EN 649	-	T
Dimensional stability	EN 434	%	≤ 0.40
Residual indentation (exigency)	EN 433	mm	≤ 0.10
Residual indentation (measure)	-	mm	~ 0.05
Impact sound insulation	EN ISO 717-2	dB	5
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	-	OK
Anti-bacterial and fungicidal treatment	-	-	Sanosol®
Surface treatment	-	-	PUR

CE MARKING


CE	EN 14041	-			
		-			

INSTALLATION

Laying is under the responsibility of installer. Installation has to be in accordance with the state of art. Technical installation guidelines are available from our technical department. Subfloor to be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate an effective Damp Proof Membrane. The material must be allowed to acclimatise 24 hours before installation in a room temperature of between 18-24°C. All seams must be heat welded using Gerflor weld rod.

MAINTENANCE

Maintenance should be carried out regularly to retain the appearance and durability of the floor. The floorcovering should be maintained with regular sweeping and damp mopping using a neutral cleanser, or machine scrubbing with an appropriate pad. Further maintenance instructions are available upon request.

 Rubber leaves indelible stains on vinyl flooring: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide.

The images of floorcoverings in this catalogue have been reproduced as faithfully as printing technology permits.



COMMITTED TO SUSTAINABLE DEVELOPMENT

Gerflor recognizes the importance of being proactive and creating new ways to achieve sustainable development. This is why Gerflor is devoting substantial resources to environmental research.

Gerflor achievements can be summarized as follows:

HEALTH & SAFETY

Vinyl is a safe material largely used in the automotive, food packaging, healthcare and construction industries and for tools, medical disposables, which come into close and intimate contact with humans.

Gerflor uses the same grade of material to produce its floorcoverings.

- **No heavy metals, no solvent based inks, no phthalates and components rated as carcinogenic, no formaldehydes, no PCP.**
- No substance potentially subject to any REACH (Registration, Evaluation and Authorisation of Chemical) restrictions.
- **Low VOC emissions:** on average more than 70 % lower than European standards.
- **Fire resistance:** vinyl does not help fire spread and does not release toxic gases like chloride (Cl₂) and far less carbon monoxide (CO) than any other type of flooring.



Health & Safety



Committed for future generation




Recycling

RECYCLING

Vinyl is one of the only building materials that is **100% recyclable**. As a specialist vinyl flooring manufacturer, Gerflor has developed recycling programs for:

- **Post industrial waste recycling:** almost 100% of our manufacturing waste is recycled.
- **Post installation waste recycling:** In Europe Gerflor has started to organize the collection of post installation waste from large projects for recycling.
- **Post consumer waste recycling:** Gerflor vinyl floorings are fully recyclable at the end of their life and qualify for credits under many internationally accredited Green Building Schemes.



Second life product: It used to be a vinyl floor...



ISO 14001

ISO 14001

In Europe, less than 50% of manufacturers have achieved an ISO 14001 certification and Gerflor is one of them. Gerflor industrial sites are certified ISO 14001 and are committed to continuously improving their environmental performance in terms of: air protection, reduction of energy consumption.



Gerflor Tarare manufacturing plant



Life Cycle Analysis

LIFE CYCLE ANALYSIS

Life Cycle Analysis is regarded as the ultimate means by which all environmental impacts are measured and improved upon during a product's life cycle. This assessment includes manufacture, delivery, installation, cost of ownership and maintenance, ultimate disposal and recycling of all products.

All new Gerflor product ranges are developed using a full life cycle analysis model.

- In Europe, Gerflor is actively involved with the ERFMI (European Resilient Flooring Manufacturer Institute) in preparing EU wide Life Cycle Assessment of a broad range of flooring types and specifications. From this study, a series of Environmental Product Declarations have been produced.
- In France, Gerflor has been involved with the SFEC to meet the HQE requirements.
- In the UK, all Gerflor products which match the BRE generic flooring specifications have been given either A or A+ ratings, with A+ representing the lowest environmental impact possible.



FDES: Environmental Product Declaration in France



green building council australia
MEMBER



DGNB
Deutscher Green Building Council



Dutch Green Building Council



ARBEITSGEMEINSCHAFT
PVC UND UMWELT E.V.



floor score

gerflor.com

ARCHITECTURE
DECORATION
SPORT
TECHNOSPECIFIC

ASIA: Gerflor Asia

Tel: +852 9222 6355 - Fax: +852 3006 1449

e-mail: gerflorasiasia@gerflor.com

AUSTRALIA/NEW ZEALAND: Gerflor Australasia Pty. Ltd

Australia Tel: 1 800 060 785 - New Zealand Tel: 0 800 630 119

e-mail: gerflor@gerflor.com.au

AUSTRIA/SWITZERLAND: Gerflor GmbH

Tel: +43 (0)72 29/70 800-0 - Fax: +43 (0)72 29/70 800-218

e-mail: austria@gerflor.com - switzerland@gerflor.com

BELGIUM/LUXEMBURG: Gerflor Benelux

Tel: +32 (0)3 766 42 82 - Fax: +32 (0)3 766 29 14

e-mail: gerflorbelgium@gerflor.com

CANADA: Gerflor International

Tel: +1 450 538 9828 - Fax: +1 450 538 9827

e-mail: gerflorcanada@gerflor.com

CHINA: Gerflor China

Tel: +86 21 6357 8818 - Fax: +86 21 6357 8998

e-mail: gerflorchina@gerflor.com

FINLAND : Gerflor OY

Tel: +358 (0) 10 617 5150 - Fax: +358 (0) 10 617 5152

e-mail: info@gerflor.fi

FRANCE: Gerflor - Service Express:

► N°Azur 0 810 569 569 ◀ ◀ N°Azur FAX 0 810 569 570 ▶

PREX APPEL LOCAL

PREX APPEL LOCAL

e-mail: contactfrance@gerflor.com

GERMANY: Gerflor Mipolam GmbH

Tel: 0 22 41-25 30-0

e-mail: GerflorMipolam@Gerflor.com

Kunden-Service: kundenservice@gerflor.com

Tel: 0 22 41-25 30-131 - Fax: 0 22 41-25 30-100

SAT Service und Anwendungstechnik: Technik@Gerflor.com

Tel: 0 22 41-25 30-555 - Fax: 0 22 41-25 30-550

IRELAND: Gerflor Ltd

Tel: +353 (0) 42 966 1431 - Fax: +353 (0) 42 966 1759

e-mail: gerflorirl@gerflor.com

ITALY: Gerflor S.p.A.

Tel: +39 02 90 78 60 12 r.a. - Fax: +39 02 90 42 74 84

e-mail: gerfloritalia@gerflor.com

LATIN AMERICA (Brazil): Gerflor América Latina

Tel: +55 11 38 48 20 20 - Fax: +55 11 38 48 20 23

e-mail: gerflor@gerflor.com.br

MIDDLE EAST: Gerflor Middle East

Tel: +966 3 847 1779 - Fax: +966 3 847 1781

e-mail: gerflorME@gerflor.com

NETHERLANDS: Gerflor BV

Tel: +31 (0)40 266 17 00 - Fax: +31 (0)40 257 46 89

e-mail: gerflorNL@gerflor.com

OTHER COUNTRIES: Gerflor International

Tel: +33 (0)4 74 05 40 00 - Fax: +33 (0)4 74 05 03 13

e-mail: gerflorcontract@gerflor.com

POLAND: Gerflor Polska Sp z o.o

Tel: + 48 61 823 34 01 - Fax: + 48 61 823 34 33

e-mail: info@gerflor.pl

PORTUGAL: Gerflor Iberia, SA

Tel: +351 21 843 95 49 - Fax: +351 21 846 55 44

e-mail: gerflorportugal@gerflor.com

RUSSIA: Gerflor Moscow Office

Tel: + 7 495 430-86-54 / 65 - Fax: + 7 495 430-85-46

e-mail: gerflorrus@mspk.east.ru

SCANDINAVIA: Gerflor Scandinavia a.s.

Tel: + 47 64 95 60 70 - Fax: + 47 64 95 60 80

e-mail: gerflorscand@gerflor.no

SPAIN: Gerflor Iberia, SA

Tel: +34 91 653 50 11 - Fax: +34 91 653 25 85

e-mail: gerfloriberia@gerflor.com

UNITED KINGDOM: Gerflor Ltd

Sample service: Contractuk@gerflor.com

Office Tel: + 44 (0) 1926 622 600 - Fax: +44 (0) 1926 622 616

USA: Gerflor North America

Tel: 877 GERFLOR [437 3567] - Fax: 847 394 3753

e-mail: info@gerflorusa.com




Health
& Safety



ISO 14001



Recycling



LCA
Life Cycle
Analysis

Committed to sustainable development

Gerflor[®]
theflooringgroup