

SELF-ADHESIVE VINYL TILES AND PLANKS

BENEFITS

QUICK AND EASY INSTALLATION

• No gluing: self-adhesive system

 No tools needed: can be trimmed with an utility knife

IDEAL FOR RENOVATIONS

2 mm thick: doors don't have to be shortened

REALISTIC

Textured, matt finish surface 4 bevelled edges

SUITABLE FOR HIGH-HUMIDITY ROOMS

Watertight and slip-resistant

EASY TO CLEAN, ECONOMICAL AND ECO-FRIENDLY

Clean with soapy water or neutral detergent



TECHNICAL CHARACTERISTICS



		Planks	Tiles			
THICKNESS	mm	2	2			
WEAR LAYER THICKNESS	mm	0,2	0,2			
WEIGHT	g/m²	3920	3425			
DIMENSIONS	cm	91,4 x 18,4	30,5 x 60,9			
AREA PER BOX	m²	2,69	2,22			
TILES & PLANKS PER BOX	Planks / Tiles	16	12			
SURFACE		Varnished	Varnished			
EUROPEAN CLASSIFICATION	Class	22	22			
FIRE RATING	Class	BflS1	BflS1			
SOUND INSULATION	dB	3	3			
WATER RESISTANCE		Compatible with wet rooms				
RESIDENTIAL USE GUARANTEE*	Years	10	10			

^{*} For more details on guarantee, see www.gerflor.com



SELF-ADHESIVE VINYL TILES AND PLANKS

INSTALLATION TIPS

- TOOLS REQUIRED: ruler, utility knife, tape measure
- Check that all planks have the same batch number
- Store the planks in the room, flat and face up, for 24 hours prior to installation

SU	DD	ΛP	T	TΠ	ΙF	D٨	NΙ	7
20		υĸ		ıυ	ᆫ	КΑ	IVI	. E

Flatness tolerance Step tolerance

INSTALLATION
POSSIBILITIES
ACCORDING
TO SUBFLOOR*

On carpet

On seamless tile (granite-type)

On tile (with joints)

On laminate

On concrete

On PVC (compact)

On solid or engineered wood floor with ventilated underside

HEATED FLOORING

> 28°C

< 28°C

Reversible

Anhydrite coating

EXPOSURE

Veranda Skylight The subfloor must be smooth, hard, dry and clean

No Remove subfloor

Yes

No Resurfacing required

No Remove subfloor

Yes, if original surface is smooth

No Remove subfloor Under certain conditions (see warning)

No

Yes

No

Under certain conditions (see warning)

Νo

Νo

^{*} For more details on installation, see instructions on www.gerflor.com



TECHNICAL TIP:

For an effective lasting adhesion, subfloors must be primed using a Gerflor primer prior to installation.



ENVIRONMENT



HEALTH

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer
- Low VOC emission

ENVIRONMENT

- 100% recyclable
- Soapy water cleaning