

TARALAY EMOTION™

gerflor.com
gerflor.asia




Gerflor®
theflooringgroup

TARALAY EMOTION™



PANAME - 0802 Light Grey



BORGO - 0607 Fumee



PANAME - 0804 Slate



COUTURE - 0707 Natural



BORGO - 0606 Gris



COUTURE - 0708 Dark



PANAME - 0806 Anthracite

THE FRENCH TOUCH



COUTURE - 0710 Beige



COUTURE - 0709 Cotton




PANAME - 0811 Calaité



PANAME - 0805 Brown



PANAME - 0809 Clay



COUTURE - 0712 Smoke

TARALAY EMOTION™



PANAME - 0810 Jade

THE
FRENCH
TOUCH



BORG0 - 0611 Pearl



COUTURE - 0711 Capuccino



BORG0 - 0601 Azur



COUTURE - 0713 Sky



COUTURE - 0714 Iris

EARTH / PASTELS



COUTURE - 0701 Ivory



BORGO - 0603 Sand



PANAME - 0801 Sable



BORGO - 0608 Pastel

TARALAY EMOTION™



PANAME - 0808 Ocre



PANAME - 0807 Yellow



BORG0 - 0602 Sahara




COUTURE - 0715 Corn



BORG0 - 0616 Beige



BORGO - 0619 Purple



BORGO - 0612 Sapphire



BORGO - 0615 Verdure



THE
FRENCH
TOUCH



BORGO - 0618 Blowe



BORGO - 0620 Grass



BORGO - 0614 Inulin



BORGO - 0617 Redish



TARALAY EMOTION™



WOOD FONTENAY - 0506 Exotic



WOOD FONTENAY - 0505 Brown



WOOD AMBOISE - 0902 Rustic



WOOD AMBOISE - 0903 Beige



WOOD AMBOISE - 0901 Black



No plank
continuous
design

WOOD ARCY - 1002 Taupe



WOODS



WOOD AMBOISE - 0904 White



WOOD FONTENAY - 0504 Cream



WOOD CHINON - 0402 Light



WOOD CHINON - 0403 Honey



WOOD FONTENAY - 0503 Honey



WOOD ARCY - 1003 Chamois






Protecsol®

Sanosol

34-43

BORG / COUTURE / PANAME / WOOD

Sanosol



- ① Protecsol® surface treatment
- ② Transparent wear layer
- ③ Printed design
- ④ Fiber glass reinforced layer
- ⑤ Compact back layer

- ☐ Protecsol® surface treatment with excellent resistance to scratching, scuffing & easy cleaning.
- ☐ Sanosol treated throughout the thickness to prevent bacterial and fungicidal contamination.
- ☐ Transparent wear layer with printed designing, highest durability.
- ☐ No DOP, no heavy-metal, no benzene, no formaldehyde & 100% compliant with REACH, friendly to health and environment.
- ☐ Compact backing with fiber glass reinforced layer. High resistance to static and dynamic perforation under rolling loads, and excellent dimensional stability.
- ☐ Recommended for high traffic area in education, office, retail, hospital and institutional buildings.



Compact sheet, without foam backing

FEWER VOC'S, BETTER INDOOR AIR QUALITY



COMPOSITION 100% REACH compliant

- FREE of formaldehyde
- FREE of heavy metals
- FREE of solvent



WELLNESS

Health

- Antibacterial activity (inhibits growth > 99 %)



INDOOR AIR QUALITY

- TVOC emissions 100 times lower than norm requirements (TVOC < 10 µg/m³ after 28 days)
- Floorscore certified
- M1 certified
- Comply with AgBB protocol
- No formaldehyde emission



RECYCLABILITY

- 100 % recyclable product



RECYCLED CONTENT

- 100 % REACH compliant recycled content

TARALAY EMOTION™ BORGO / COUTURE / PANAME / WOOD is a multilayered compact vinyl floor covering, available in 2m width sheet, with a group T wear rating. The product comprises a printed design protected by a transparent wear layer, and a compact backing with fiber glass reinforced layer, which resists static and dynamic perforation under rolling loads and provides excellent dimensional stability.

TARALAY EMOTION™ BORGO / COUTURE / PANAME / WOOD is treated with ProtecSol® surface treatment with excellent resistance to scratching, scuffing & easy cleaning, no wax for life, and Sanosol treated throughout the thickness to prevent bacterial and fungicidal contamination. It has no DOP, no heavy-metal, no benzene, no formaldehyde & 100% compliant with REACH, which is friendly to health and environment, recommended for high traffic area in education, office, retail, hospital and institutional buildings.

INSTALLATION

Installation should be carried out in accordance with local standards. Subfloor should be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate an effective Damp Proof Membrane. The material must be allowed to acclimatize 24 hours before installation in a room temperature of between 18-24°C. All seams must be hot welded using Gerflor® matching welding rod.

MAINTENANCE

No acrylic emulsion (wax) is needed for life. Maintenance should be carried out regularly to retain in the appearance and durability of the floor. The floorcovering should be maintained with regular sweeping and damp mopping using a neutral cleanser. More intense cleaning should be carried out using a fine spray cleaning pad under a floor machine, or for larger areas combined machine cleaning.

TARALAY EMOTION™ BORGO / COUTURE / PANAME / WOOD

DESCRIPTION				
Total thickness	ISO 24346 (EN 428)	mm	2.0	2.6
Thickness of wearlayer	ISO 24340 (EN 429)	mm	0.7	0.7
Weight	ISO 23997 (EN 430)	g/m²	2800	3800
Sheet of Width / Length	ISO 24341 (EN 426)	cm / lm	200 / 20	200 / 15
CLASSIFICATION				
Norm / Product specification	-	-	ISO 10582 (EN 649)	ISO 10582 (EN 649)
European classification	ISO 10874 (EN 685)	class	34-43	34-43
Fire rating	EN 13501 - 1	class	Bfl-s1	Bfl-s1
Static electrical propensity	EN 1815	kV	< 2	< 2
Slip resistance wet	DIN 51 130	class	R9	R9
PERFORMANCES				
Wear resistance	EN 660.2	mm³	≤ 2.0	≤ 2.0
Wear group	EN 649	group	T	T
Type binder content	ISO 10582	type	I	I
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.4	≤ 0.4
Residual indentation	ISO 24343-1 (EN 433)	mm	≤ 0.1	≤ 0.1
Castor chair test	ISO 4918 (EN 425)	-	OK	OK
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.k)	0.25	0.25
Colour fastness	ISO 105 - B02	degree	≥ 6	≥ 6
Chemical products resistance	ISO 26987 (EN 423)	-	OK	OK
Anti-bacterial and fungicidal treatment	-	-	Sanosol	Sanosol
Surface treatment	-	-	ProtecSol®	ProtecSol®
Anti-bacterial activity [E.coli - S.aureus - MRSA] (1)	ISO 22196	-	> 99 % inhibits growth	> 99 % inhibits growth
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000 - 6	µg/m³	< 100	< 100
Certification	-	-	FloorScore®	FloorScore®
CE MARKING				



EN 14041



(1) The implementation of an effective cleaning regime is the most important defence against infections.



TARALAY EMOTION BORGO



TARALAY EMOTION COUTURE





TARALAY EMOTION WOOD

ASIA: Gerflor Asia

Tel: +86 21 6357 8818 - Fax: +86 21 6357 8998

e-mail: gerflorasia@gerflor.com

AUSTRALIA/NEW ZEALAND: Gerflor Australasia Pty. Ltd

Australia Tel: 1 800 060 785 - New Zealand Tel: 0 800 630 119

e-mail: gerflorid@gerflor.com.au

AUSTRIA/SWITZERLAND: Gerflor GmbH

Tel: +43 (0)72 29/70 800-0 - Fax: +43 (0)72 29/70 800-218

e-mail: austria@gerflor.com - switzerland@gerflor.com

BELGIUM/LUXEMBURG: Gerflor Benelux

Tel: +32 (0)3 766 42 82 - Fax: +32 (0)3 766 29 14

e-mail: gerflorbel@gerflor.com

CANADA: Gerflor International

Tel: +1 438 333 0752 - Fax: +1 438 380 5425

e-mail: gerflorcanada@gerflor.com

CHINA: Gerflor Floorings [China] Co., Ltd.

Tel: +86 21 6357 8818 - Fax: +86 21 6357 8998

e-mail: gerflorchina@gerflor.com

FINLAND: Gerflor Oy

Tel: +358 (0) 10 6 17 5150 - Fax: +358 (0) 10 617 5152

e-mail: info@gerflor.fi

FRANCE: Gerflor - Service Express**0 810 569 569** **0 810 569 570**

e-mail: contactfrance@gerflor.com

GERMANY: Gerflor Milopol GmbH

Tel: +49 (0)22 41-25 30-0

e-mail: gerflormilopol@gerflor.com

Kunden-Service

Tel: +49 (0) 22 41-25 30-136 - Fax: +49 (0) 22 41-25 30-100

e-mail: kundenservice@gerflor.com

SAT Service und Anwendungstechnik

Tel: +49 (0)22 41-25 30 555 - Fax: +49 (0)22 41-25 30 550

e-mail: technik@gerflor.com

IRELAND: Gerflor Ltd

Tel: +353 (0) 42 966 1431 - Fax: +353 (0) 42 966 1759

e-mail: gerfloriri@gerflor.com

ITALY: Gerflor S.p.A.

Tel: +39 02 90 40 10 - Fax: +39 02 90 42 74 84

e-mail: gerfloritalia@gerflor.com

LATIN AMERICA (Brazil): Gerflor América Latina

Tel: +55 11 38 48 20 20

e-mail: gerflor@gerflor.com.br

MIDDLE EAST: Gerflor Middle East

Tel: +966 13 847 1779 - Fax: +966 13 847 1781

e-mail: info@gerflorme.com

NETHERLANDS: Gerflor Benelux

Tel: +31 (0)40 266 17 00 - Fax: +31 (0)40 257 46 89

e-mail: gerflornl@gerflor.com

OTHER COUNTRIES: Gerflor International

Tel: +33 (0)4 74 05 40 00 - Fax: +33 (0)4 74 05 03 13

e-mail: gerflorcontract@gerflor.com

POLAND: Gerflor Polska Sp z o.o

Tel: +48 61 823 34 01 - Fax: +48 61 823 34 33

e-mail: info@gerflor.pl

PORTUGAL: Gerflor Iberia, SA

Tel: +351 21 842 95 49 - Fax: +351 21 846 55 44

e-mail: gerflorportugal@gerflor.com

RUSSIA: Gerflor zao

Tel./Fax: +7 495 785 23 71

e-mail: gerflorrussia@gerflor.ru

SCANDINAVIA: Gerflor Scandinavia a.s.

Tel: +47 64 95 60 70 - Fax: +47 64 95 60 80

e-mail: gerflorscand@gerflor.no

SPAIN: Gerflor Iberia, SA

Tel: +34 91 653 50 11 - Fax: +34 91 653 25 85

e-mail: gerfloriberia@gerflor.com

UNITED KINGDOM: Gerflor Ltd

Sample service: Contractuk@gerflor.com

Office Tel: +44 (0) 1926 622 600 - Fax: +44 (0) 1926 401 647

USA: Gerflor North America

Tel: 877 GERFLOR (437 3567) - Fax: 847 394 3753

e-mail: info@gerflorusa.com

gerflor.com

gerflor.asia

**ARCHITECTURE
DECORATION
SPORT
TECHNOSPECIFIC**MAR 2018-03-15 Version indicative documentation cost USD 0.9
Gerflor has a policy of continuous product improvement. It reserves the right to change design and specifications without notice.**Gerflor** *Don't forget* our complementary ranges!

Handrails

Wall Coverings
& Protections

Entrance mats



Skirtings & Profiles

and Be CONNECTED!

www.gerflor.com

Health
& Safety

ISO 14001



Recycling

LCA
Life Cycle
Analysis

Committed to sustainable development

Gerflor®
theflooringgroup