

# **CLEANING LVT**

TOPSILENCE DESIGN



#### Mechanical dust removal equipments Vacuum



#### Manual washing equipment Disposable microfibre mop or gauze



#### Damp sweeping equipment

Flexible mop preferably fitted with disposable, antistatic and/or pre-impregnated gauze strips

On Topsilence Design, the solution to dwell is strictly forbidden. Do not use large amounts of water when cleaning and avoid any access moisture.

|   | Equipment used | Cleaning products  | Cleaning methods   |
|---|----------------|--------------------|--|
| First use or Deep Cleaning  Mechanical cleaning |                | Alkaline detergent | Vacuum Damp sweeping Manual washing with flat mop Rinsing Don't leave any puddles or excess of water on surface    |
| Daily cleaning  Manual cleaning                 |                | Neutral detergent  | Vacuum  Damp sweeping  Manual washing with flat mop Rinsing  Don't leave any puddles or excess of water on surface |

In the case of manual maintenance and to offer you the best results in terms of hygiene and appearance, Gerflor recommends that you use neutral and alkaline detergents with high wetting power (complete spreading and cleaning of the entire floor surface).

PH neutral detergent: non-greasy soaps like green soap or non-soaps that build film.

# Gerflor theflooringroup

# STAIN REMOVAL

# PRECAUTIONS FOR USE



- Never use abrasive disks or any procedure that risks damaging the surface treatment (abrasive products, solvents, etc.).
- Never use rubber caps (for chair legs or other furniture); instead, use PVC or Polyethylene caps.

# STAIN REMOVAL DURING WORKS

#### Paint mark removal

- Do not use abrasive cleaning equipment (e.g. Scotch Brite, scouring pads, steel wool, etc.).
- Use the solvent for the paint if known. If the solvent is not known, start with solvents such as Essence C, White Spirit, etc. before trying stronger solvents such as Taraclean spray. If the stain proves hard to remove, do not persist.
- Wipe and rinse the floor thoroughly after applying the solvent.

#### On paint drips

A freeze spray will yield excellent results when paint has formed a drip on the material (freeze sprays can be bought from cleaning product manufacturers or in pharmacies).

#### On adhesive marks

Fresh acrylic adhesive marks (< 1 month)</li>

Apply a water-based solution with added cleaning product, leave to act and mechanically clean and rinse the floor.

Dried acrylic adhesive marks (> 1 month)

Use Essence C or White Spirit. Wipe and rinse the floor thoroughly after applying the solvent.

Solvent adhesive marks

Use strong solvents (such as Taraclean spray), but do not persist if the adhesive marks are difficult to remove (as may happen with solvent-resistant cross-linked adhesives).

# TIPS AND ADVICE FOR STAIN REMOVAL

#### Rust

Apply an anti-rust product or oxalic acid. Rinse thoroughly.

### Food grease/paint/ballpoint pen/felt-tip pen/heavy grease (tar)

Apply a solvent such as Essence C or White Spirit. Rub with undiluted product and rinse with plenty of water.

#### Rubber marks/Shoe marks

Apply an alkaline detergent (such as Dynatech Trophy) to shoe marks. Leave to act for 5 minutes. Rub.

#### Chewing-gum

Use a freeze spray to harden the chewing gum, and then remove it with a plastic spatula (freeze sprays can be bought from cleaning product manufacturers or in pharmacies).