

**DESCRIPTION**

Total thickness	EN ISO 24346	mm	2.00
Weight	EN ISO 23997	g/m <sup>2</sup>	3360
Width of sheet	EN ISO 24341	cm	200
Length of sheet	EN ISO 24341	lm	20

**CLASSIFICATION**

Norm / Product specification	-	-	EN ISO 10581
European classification	EN ISO 10874	class	34 - 43
Fire rating	EN 13 501-1	class	B <sub>fl</sub> -s1
Static electrical propensity	EN 1815	kV	< 2

**PERFORMANCE**

Type Binder content	EN ISO 10581	type	II
Dimensional stability	EN ISO 23999	%	≤ 0.40
Residual indentation	EN ISO 24343-1	mm	~ 0.03
Castor chair test (type W)	ISO 4918	-	OK
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	EASYCARE™
Chemical products resistance	EN ISO 26987	class	OK

**ENVIRONMENT / INDOOR AIR QUALITY**

TVOC after 28 days	ISO 16000-6	µg/ m <sup>3</sup>	< 10
Certification	-	-	Floorscore®