

DESCRIPTION

Total thickness	EN ISO 24346 (EN 428)	mm	2.00
Weight	EN ISO 23997 (EN 430)	g/sqm	3100
Width of sheet	EN ISO 24341 (EN 426)	cm	200
Length of sheet	EN ISO 24341 (EN 426)	lm	20
Tile size	EN ISO 24342 (EN 427)	mm	608*608
Number of tiles per package	-	-	20

CLASSIFICATION

Standard / Product specification		-	EN ISO 10581 (EN 649)
European classification	EN ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13501-1	class	Bfl-s1
Electrical resistance (1)	EN 1081	Ohm	$10^6 \leq R_t \leq 10^8$
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet	DIN 51130	Class	R9






PERFORMANCE

Wear resistance	EN 660.2	mm ³	≤ 4.0
Wear group	NF 189	group	P
Type Binder content	EN ISO 10581	type	II
Dimensional stability	EN ISO 23999 (EN 434)	%	sheet ≤ 0,40 tile ≤ 0.25
Residual indentation	EN ISO 24343-1 (EN 433)	mm	~ 0,02
Castor chair test (type W)	ISO 4918 (EN 425)	-	OK
Thermal conductivity	EN ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	Evercare™
Chemical products resistance	EN ISO 26987 (EN 423)	-	OK

ENVIRONMENT / INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
Certification	-	-	Floorscore®

MARQUAGE CE

	EN 14041	-	 ≤10 ⁹ Ω	 DS	
		-		 Bfl-s1	

(1) Measured before installation