

DESCRIPTION

Total thickness	EN ISO 24346 (EN 428)	mm	2.00
Weight	EN ISO 23997 (EN 430)	g/m ²	3300
Width of sheet	EN ISO 24341 (EN 426)	cm	200
Length of sheet	EN ISO 24341 (EN 426)	lm	20
Tile size	EN ISO 24342 (EN 427)	mm	608 x 608
Number of tiles per package		-	20

CLASSIFICATION

Standard / Product specification	-	-	EN ISO 10581 (EN 649)
European classification	EN ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13501-1	class	B _{f1} -s1
Electrical resistance (1)	EN 1081	Ohm	$10^6 \leq R_t \leq 10^8$
Static electrical propensity	EN 1815	kV	< 2






PERFORMANCE

Wear resistance	EN 660.2	mm ³	≤ 7.5
Wear group	NF 189	group	M
Type Binder content	EN ISO 10581	type	II
Dimensional stability	EN ISO 23999 (EN 434)	%	sheet ≤ 0.40 tile ≤ 0.25
Residual indentation	EN ISO 24343-1 (EN 433)	mm	$\sim 0,03$
Castor chair test (type W)	ISO 4918 (EN 425)	-	OK
Thermal conductivity	EN ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN ISO 26987 (EN 423)	-	OK

ENVIRONMENT / INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000-6	$\mu\text{g}/\text{m}^3$	< 10
--------------------	-------------	--------------------------	------

CE MARKING

	EN 14041	-	  
		-	

(1) Measured before installation