




	MIPOLAM SYMBIOZ		
DESCRIPTION			
Total thickness	EN ISO 24346 (EN 428)	mm	2.00
	ASTM F386-02	inch	0.08
Weight	EN ISO 23997 (EN 430)	g/sq.m	2580
Width of sheet	EN ISO 24341 (EN 426)	cm	200
	-	feet - inch	6'6"
Length of sheet	EN ISO 24341 (EN 426)	lm	20
	-	feet - inch	66'
Coverage / roll	-	sq.ft	430.56
	-	sq.m	40
CLASSIFICATION			
Norm / Product specification	-	-	EN ISO 10581 (EN 649)
	ASTM F 1913-04		compliant
European classification	EN ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13 501-1	class	Br-s1
	ASTM E648-08	class	Class I
	CAN/ULC S102.2	-	tested in accordance
Static electrical propensity	EN 1815	kV	< 2
PERFORMANCE			
Wear resistance	EN 660.2	mm ³	≤ 2.0
Wear Group	NF 189	group	T
Type Binder content	ISO 10581	type	I
Dimensional stability	EN ISO 23999 (EN 434)	%	≤ 0.40
Impact sound insulation	EN ISO 717-2	dB	5
Residual indentation	EN ISO 24343-1 (EN 433)	mm	~ 0.02
Castor chair test (type W)	ISO 4918 (EN 425)	-	OK
Thermal conductivity	EN ISO 10456 (EN 12 524)	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	Evercare™
Chemical products resistance	EN ISO 26987 (EN 423)	class	OK
Anti-bacterial activity (E. coli – S. aureus – MRSA) *	ISO 22196	-	> 99% inhibits growth
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
Certification	-	-	Floorscore®
CE MARKING			
	EN 14041	-	  
		-	

* The implementation of an effective cleaning method is the best defence against infection