






DESCRIPTION			
Total thickness	EN ISO 24346 (EN 428)	mm	2.00
	ASTM F386-02	inch	0.08
Weight	EN ISO 23997 (EN 430)	g/m ²	3800
Tile size	EN ISO 24342 (EN 427)	mm	608*608
Number of tiles per package	-	-	20
CLASSIFICATION			
Standard / Product specification	-	-	EN ISO 10581 (EN 649)
European classification	EN ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13501-1	class	B _{fl} -s1
Electrical resistance (1)	EN 1081	Ohm	10 ⁴ ≤ Rt ≤ 10 ⁶
	IEC 61340-4-1	Ohm	≤ 10 ⁹
	ANSI / ESD STM 7.1	Ohm	≤ 10 ⁹
Static electrical propensity	EN 1815	kV	< 2
	IEC 61340-4-5	V	< 100 (2)
Protection against electrostatic discharges	ESD S20.20	-	OK
	IEC 61340-5-1	-	OK
PERFORMANCE			
Wear resistance	EN 660.2	mm ³	≤ 4.0
Wear group	NF 189	group	P
Type Binder content	ISO 10581	type	II
Dimensional stability	EN ISO 23999 (EN 434)	%	≤ 0.25
Residual indentation	EN ISO 24343-1 (EN 433)	mm	~ 0,03
Castor chair test (type W)	ISO 4918 (EN 425)	-	OK
Thermal conductivity	EN ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN ISO 26987 (EN 423)	-	OK
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
MARQUAGE CE			
	EN 14041	-	  
		-	

(1) Measured before installation

(2) Measured with ESD shoes (ABEBA and Uvex)