

BORGIO / COUTURE / PANAME / WOOD

DESCRIPTION

Total thickness	EN 428	mm	2.0	2.6
Thickness of wearlayer	EN 429	mm	0.7	0.7
Weight 重量	EN 430	g/m ²	3100	4000
Width of sheet	EN 426	cm	200	200
Length of sheet	EN 426	lm	20	15

CLASSIFICATION

Norm / Product specification	-	-	EN 649	EN 649
European classification	EN 685	class	34-43	34-43
Fire rating(EN)	EN 13 501-1	class	Bfl-s1	Bfl-s1
Static electrical propensity	EN 1815	KV	< 2	< 2
Slip resistance wet	DIN 51 130	class	R9	R9






PERFORMANCE

Abrasion resistance	EN 660.2	mm ³	≤ 2	≤ 2
Abrasion group	EN 649	group	T	T
Type binder content	ISO 10582	typ	I	I
Dimensional stability	EN 434	%	≤ 0.4	≤ 0.4
Residual indentation	EN 433	mm	≤ 0.1	≤ 0.1
Castor chair test	EN 425	-	OK	OK
Thermal conductivity	EN 12 524	W/(m.K)	0.25	0.25
Colour fastness	ISO 105 - B02	degree	≥ 6	≥ 6
Chemical products resistance	EN 423	-	Good	Good
Special maintenance treatment	-	-	Protecsol™	Protecsol™
Anti-bacterial activity (E.coli - S.aureus - MRSA) (1)	ISO 22196	-	> 99% inhibits growth	> 99% inhibits growth

ENVIRONMENT / INDOOR AIR QUALITY

TVOC* after 28 days	ISO 16000 - 6	µg/m ³	<100	<100
Certification	-	-	Floorscore®	Floorscore®

CE MARKING 标识

	EN 14041	   
---	----------	--

(1) The implementation of an effective cleaning regime is the best defence against infections.