

CLEANING SEMI-CONTRACT FLOORS

SENSO / VIRTUO / PRIMETEX / TEXLINE / TEXLINE PRO / TEXLINE HQR / HOME COMFORT / SOLIDTEX / TURBO / BOOSTER / EVREST / AGRIPPA



Manual dust removal equipments



Mechanical dust removal equipments



Manual washing equipments Damp mop



Manual washing equipments

Disposable microfibre mop or gauze

| | | Equipment used | Cleaning products | Cleaning methods |
|---------------------------|--------|----------------|---|--|
| First use Manual cl | eaning | or Jo | Standard detergent / Restorative product | Dust removal by mop or vacuum Wash with damp mop and standard detergent Application of the restorative product with a wiper mop Allow the floor surface to dry before to use it again. |
| Daily cleaning Manual cl | eaning | or Design | Standard detergent | Dust removal by mop or vacuum Wash with damp mop and standard detergent. |
| Deep cleaning Manual cl | eaning | or John Market | Standard detergent / Restorative product | Dust removal by mop or vacuum Wash with damp mop and standard detergent Application of the restorative product with a wiper mop Allow the floor surface to dry before to use it again. |

In the case of manual maintenance and to offer you the best results in terms of hygiene and appearance, Gerflor recommends that you use the standard detergent POWER CLEANER and the restorative product RENOVATOR POLISH (complete spreading and cleaning of the entire floor surface).



Products to avoid: acetone, chlorinated solvents such as trichlorethylene, wax, glaze.

POWER CLEANER



| Product code per unit | Gencod per unit | | Per carton | |
|--------------------------|--------------------|---|---------------|--|
| 06130001 | 3475710290206 | 1 | 5 units of 1L | |

RENOVATOR POLISH



| Product code per unit | Gencod per unit | 1 | Per carton |
|--------------------------|--------------------|---|---------------|
| 06140001 | 3475710290213 | 1 | 5 units of 1L |

Gerflor theflooringroup

STAIN REMOVAL

PRECAUTIONS FOR USE



- Never use abrasive disks or any procedure that risks damaging the surface treatment (abrasive products, solvents, etc.).
- Never use rubber caps (for chair legs or other furniture); instead, use PVC or Polyethylene caps.

STAIN REMOVAL DURING WORKS

Paint mark removal

- Do not use abrasive cleaning equipment (e.g. Scotch Brite, scouring pads, steel wool, etc.).
- Use the solvent for the paint if known. If the solvent is not known, start with solvents such as Essence C, White Spirit, etc. before trying stronger solvents such as Taraclean spray. If the stain proves hard to remove, do not persist.
- Wipe and rinse the floor thoroughly after applying the solvent.

On paint drips

A freeze spray will yield excellent results when paint has formed a drip on the material (freeze sprays can be bought from cleaning product manufacturers or in pharmacies).

On adhesive marks

Fresh acrylic adhesive marks (< 1 month)

Apply a water-based solution with added cleaning product, leave to act and mechanically clean and rinse the floor.

Dried acrylic adhesive marks (> 1 month)

Use Essence C or White Spirit. Wipe and rinse the floor thoroughly after applying the solvent.

Solvent adhesive marks

Use strong solvents (such as Taraclean spray), but do not persist if the adhesive marks are difficult to remove (as may happen with solvent-resistant cross-linked adhesives).

TIPS AND ADVICE FOR STAIN REMOVAL

Rust

Apply an anti-rust product or oxalic acid. Rinse thoroughly.

Food grease/paint/ballpoint pen/felt-tip pen/heavy grease (tar)

Apply a solvent such as Essence C or White Spirit. Rub with undiluted product and rinse with plenty of water.

Rubber marks/Shoe marks

Apply an alkaline detergent (such as Dynatech Trophy) to shoe marks. Leave to act for 5 minutes. Rub.

Chewing-gum

Use a freeze spray to harden the chewing gum, and then remove it with a plastic spatula (freeze sprays can be bought from cleaning product manufacturers or in pharmacies).