


	PRODUCT CHARACTERISTICS			
	Standard	Requirement	Unit	Results
	PRODUCT DESCRIPTION			
Surface treatment	-	-	-	Protecsol
Surface complex	-	-	-	D-max
Foam	-	-	-	Double-density CXP-HD
Thickness	EN ISO 24346	-	mm	9,35
Weight	EN ISO 23997	-	kg/m ²	5.2
Length	EN ISO 24341	-	lm	26,5 max
Width	EN ISO 24341	-	lm	1,5
	SPORT PROPERTIES			
Shock absorption	EN 14808	≥ 35	%	P2
Vertical deformation	EN 14809	≤ 3,5	mm	≤ 3
Sliding coefficient	EN 13036-4	80 - 110	-	80 - 110
Ball bounce	EN 12235	≥ 90	%	≥ 90
	TECHNICAL CHARACTERISTICS			
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	N/m	≥ 8
Indentation resistance	EN 1516	≤ 0,5	mm	≤ 0,5
Impact sound insulation	EN ISO 717-2	-	dB	21
	CLASSIFICATION			
Fire (looselay on concrete)	EN 13501-1	-	-	Cfl,s1
Anti-bacterial activity (E. coli - S. aureus - MRSA) (1)	ISO 22196			> 99 % inhibits growth
	DECLARATION OF PERFORMANCE			
	DOP-005-1047	-	-	Fire Shock Absorption Sliding Coefficient Abrasion Resistance Rolling Load Resistance

(1) The implementation of an effective cleaning method is the best defence against infection